

NVR-8108G-P4



P2P Mobile App:
VSSMOBILE



CPCAM 4CH POE H.265 UHD 5MP NVR- 4K Output

FEATURES

- Support H.265/H.264 IP camera
- Input 8ch 5MP/4MP/2MP IP camera
- HDMI® and VGA resolution up to 4K
- Smart face detection and Perimeter detection
- 4 POE ports support standard 802.3af
- On-board 1 SATA port
- ONVIF 2.4 supported and compatible with almost all third-party IP cameras
- 3D intelligent PTZ control via USB Mouse
- Built-in P2P Cloud service, firewall penetration automatically
- Mass of network protocols NTP, Email, RTSP, UPNP
- Support iPhone, Android APP
- Internet Explorer, Firefox and center monitoring client supported

➤ SPECIFICATIONS

▼ Input

| | |
|-------------------|--------------------------------------|
| IP Camera Input | 8 channel |
| Handling Capacity | 60Mbps |
| Audio In | G711A@64Kbps(need IP camera support) |
| Talk-back | 1 RCA |

▼ Output

| | |
|--------------|--|
| Interface | 1 HDMI, 1 VGA |
| Resolution | 3840x2160(4K) / 1920x1080 / 1280x1024 / 1280x720 / 1024x768 |
| Screen Split | 1/4/8/9 |
| Audio Out | 1 RCA |

▼ Record

| | |
|-------------|---|
| Compression | H.265 / H.264 |
| Resolution | 5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF |
| Bit Rate | 64~ 6144kbps |
| Record Mode | Manual, Schedule, MD, Alarm, Stop |

▼ Alarm

| | |
|------------------|--|
| Smart Detection | 1-ch face detection or 1-ch Perimeter detection |
| Trigger Event | Alarm, Recording, PTZ movement, Video Push out, Capture, Send Email, FTP, Buzzer , etc. |
| Video Detection | Motion Detection, MD Zones: grid 22x18, Video Loss |
| Alarm Pre-record | 1~30 seconds adjustable |
| Alarm Input | NO |
| Alarm Output | NO |

▼ Playback & Backup

| | |
|-------------------|--|
| Sync Playback | 1/4/8 |
| Playback Function | Timeline Play, Pause, Stop, Rewind, Fast play, Slow play, Step, Full screen, Digital zoom |
| Backup Mode | USB / Network |

▼ Network

| | |
|------------------|--|
| Networking Style | Ethernet(RJ-45 10/100Mbps) |
| Network Function | P2P, UPNP, RTSP, UDP, SMTP, NTP, DHCP, IP Filter, PPPOE, DDNS, FTP, Alarm Server, etc. |
| Smart devices | iPhone, iPad, Android, Windows Phone, support QR Code login |

▼ Storage

| | |
|----------|---------------------|
| HDD Slot | 1 SATA ports, SMART |
| USB | 2 * USB2.0 |

▼ Others

| | |
|---------------------|--------------------------|
| Power Supply | DC 48V/1.35A |
| POE | 4 RJ-45, 802.3af |
| Total Power | ≤45W |
| Power Consumption | <10W (without HDD & POE) |
| Working Environment | -10°C ~+55°C / 10%~90%RH |
| Dimension (mm) | 215x235x45mm |

➤ REAR PANEL

