

NVR-8108G-P8



P2P Mobile App:

VSSMOBILE



CPCAM 8CH POE H.265 UHD 5MP NVR- 4K Output

FEATURES

- Support H.265/H.264 IP camera
- Input 8ch 5MP/4MP/2MP IP camera
- HDMI® and VGA resolution up to 4K
- Smart face detection and Perimeter detection
- 8 POE ports support standard 802.3af
- On-board 1 SATA port
- ONVIF 2.4 supported and compatible with almost all third-party IP cameras
- 3D intelligent PTZ control via USB Mouse
- Built-in P2P Cloud service, firewall penetration automatically
- Mass of network protocols NTP, Email, RTSP, UPNP
- Support iPhone, Android APP
- Internet Explorer, Firefox and center monitoring client supported

➤ SPECIFICATIONS

▼ Input

IP Camera Input	8 channel
Handling Capacity	60Mbps
Audio In	G711A@64Kbps(need IP camera support)
Talk-back	NO

▼ Output

Interface	1 HDMI, 1 VGA
Resolution	3840x2160(4K) / 1920x1080 / 1280x1024 / 1280x720 / 1024x768
Screen Split	1/4/8/9
Audio Out	NO

▼ Record

Compression	H.265 / H.264
Resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Bit Rate	64~ 6144kbps
Record Mode	Manual, Schedule, MD, Alarm, Stop

▼ Alarm

Smart Detection	1-ch face detection or 1-ch Perimeter detection
Trigger Event	Alarm, Recording, PTZ movement, Video Push out, Capture, Send Email, FTP, Buzzer , etc.
Video Detection	Motion Detection, MD Zones: grid 22x18, Video Loss
Alarm Pre-record	1~30 seconds adjustable
Alarm Input	NO
Alarm Output	NO

▼ Playback & Backup

Sync Playback	1/4/8
Playback Function	Timeline Play, Pause, Stop, Rewind, Fast play, Slow play, Step, Full screen, Digital zoom
Backup Mode	USB / Network

▼ Network

Networking Style	Ethernet(RJ-45 10/100Mbps)
Network Function	P2P, UPNP, RTSP, UDP, SMTP, NTP, DHCP, IP Filter, PPPOE, DDNS, FTP, Alarm Server, etc.
Smart devices	iPhone, iPad, Android, Windows Phone, support QR Code login

▼ Storage

HDD Slot	1 SATA ports, SMART
USB	2 * USB2.0

▼ Others

Power Supply	DC 48V/1.875A
POE	8 RJ-45, 802.3af
Total Power	≤68W
Power Consumption	<10W (without HDD & POE)
Working Environment	-10°C ~+55°C / 10%~90%RH
Dimension (mm)	215x235x45mm

➤ REAR PANEL

