

NVR-8216G-P16



P2P Mobile App:

VSSMOBILE



CPCAM 16CH POE H.265 UHD 5MP NVR- 4K Output

FEATURES

- Support H.265/H.264 IP camera
- Input 16ch 5MP/4MP/2MP IP camera
- HDMI® and VGA resolution up to 4K
- Smart face detection and Perimeter detection
- 16 POE ports support standard 802.3af
- On-board 2 SATA port
- ONVIF 2.4 supported and compatible with almost all third-party IP cameras
- 3D intelligent PTZ control via USB Mouse
- Built-in P2P Cloud service, firewall penetration automatically
- Mass of network protocols NTP, Email, RTSP, UPNP
- Support iPhone, Android APP
- Internet Explorer, Firefox and center monitoring client supported

➤ SPECIFICATIONS

▼ Input

IP Camera Input	16 channel
Handling Capacity	192 Mbps
Audio In	G711A@64Kbps(need IP camera support)
Talk-back	1 RCA

▼ Output

Interface	1 HDMI, 1 VGA
Resolution	3840x2160(4K) / 1920x1080 / 1280x1024 / 1280x720 / 1024x768
Screen Split	1/4/8/9/16
Audio Out	1 RCA

▼ Record

Compression	H.265 / H.264
Resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Bit Rate	64~ 8192kbps
Record Mode	Manual, Schedule, MD, Alarm, Stop

▼ Alarm

Smart Detection	1-ch face detection or 1-ch Perimeter detection
Trigger Event	Alarm, Recording, PTZ movement, Video Push out, Capture, Send Email, FTP, Buzzer , etc.
Video Detection	Motion Detection, MD Zones: grid 22x18, Video Loss
Alarm Pre-record	1~30 seconds adjustable
Alarm Input	NO
Alarm Output	NO

▼ Playback & Backup

Sync Playback	1/4/8/16
Playback Function	Timeline Play, Pause, Stop, Rewind, Fast play, Slow play, Step, Full screen, Digital zoom
Backup Mode	USB / Network

▼ Network

Networking Style	Ethernet(RJ-45 100/1000Mbps)
Network Function	P2P, UPNP, RTSP, UDP, SMTP, NTP, DHCP, IP Filter, PPPOE, DDNS, FTP, Alarm Server, etc.
Smart devices	iPhone, iPad, Android, Windows Phone, support QR Code login

▼ Storage

HDD Slot	2 SATA ports, SMART
USB	2 * USB2.0

▼ Others

Power Supply	110V~220V±10% 47Hz~63Hz
POE	8 RJ-45, 802.3af
Total Power	≤180W
Power Consumption	<20W (without HDD & POE)
Working Environment	-10°C ~+55°C / 10%~90%RH
Dimension (mm)	1U 360*311.5*48mm

REAR PANEL

