

CPC106DV



2.1 MP 1080P HD 4in1 IR Vandal Proof Dome Camera 2.8~12mm(Dual Voltage)


FEATURES

- ❖ 4-in-1 HDCVI / HDTV/ AHD / CVBS optional output
- ❖ 1/2.9" 2.1 Mega Pixels Sony CMOS sensor
- ❖ Full HD resolution 1920 x 1080P
- ❖ Ultra low illumination 0.017Lux
- ❖ Up to 300M long distance and real time monitoring
- ❖ OSD menu control up the coaxial cable (UTC)
- ❖ Day/Night (ICR), AWB, AGC, BLC, 2D/3D-DNR
- ❖ WDR, Slow-Shutter, Smart IR, Sense up, Defog
- ❖ Motion Detection, Privacy Mask, Mirror
- ❖ Lightning protection
- ❖ Strong vandal-proof housing
- ❖ 30 pcs $\phi 5$ IR Leds, IR distance 20-30 meters , 2.8 – 12 mm VF Lens
- ❖ Dual Power Voltage DC12V/AC24V Input (Auto Switching)

SPECIFICATIONS

Model	CPC106DV
Image Sensor	1/2.9" 2.1 Mega pixels SONY CMOS
Effective Pixels	1985(H)×1105 (V)
Lowest illumination	0.01Lux@ (F1.2,AGC ON) , 0 Lux with IR
Electronic Shutter	AUTO, 1/30s~1/50,000s
Video Frame Rate	PAL/NTSC: 25/30fps@1920×1080P
Video Output	1 -BNC, HDCVI / HDTV/ AHD/ CVBS , adjustable
Smart IR Control	Support
Day/Night	Auto / Color / B/W / Extend
WDR	D- WDR
Noise Reduction	2D/3D DNR
Sense Up	Support, ×30
Privacy Mask	Support 8 Zones
Defog	Support
OSD Menu	Multiple languages OSD menu control up the coaxial cable (UTC)
Other Function	AWB, AGC, BLC, HLC , Mirror, Motion Detection
Power Supply	DC12V±10%, AC24V
Power Consumption	< 5W
Working Environment	-20°C~+60°C / Less than 95%RH
IR LED	30 pcs φ5-850nm LED
IR Distance	20~30 meters
Lens	2.8-12mm VF lens
Transmission Distance	Up to 300m via 75-3 coaxial cable

* 4-IN-1 Multiply Video modes output
Support 4 HD signals switch output, AHD/HDCVI/HDTV/ CVBS, easy to use switch cable



DIMENSIONS

